



IR-SNIF-1,2,3 Quick Quote Typical Configuration

For Single Zone Applications

IR-SNIF-1,2,3 QTY: _____ Single Zone Monitor to be mounted inside your mechanical room, or outside the primary entrance.

ACC 020 QTY: _____ Combination Horn/Strobe mounted inside mechanical room. Tie strobe to low alarm relay. Tie horn to horn relay. Use high alarm relay to energize high-speed exhaust fan.

ACC 030 QTY: _____ ¼ inch OD Fire Retardant Poly Ethylene (FRPE), 250 ft. roll, (or purchase tubing locally).

ACC 026 QTY: _____ Optional: Mount a strobe only outside each entrance to the mechanical room.

***For A Quote For This Configuration, Enter Quantities And Fax This Form To (317) 248-2014**

Name _____ Position _____

Company _____

Description of Company
(Required) _____

Address _____

City _____ State _____ Zip _____

Phone (____) _____ Fax _____

E-mail _____

Comments/Instructions _____

Sentech Corporation
5745 Progress Rd.
Indianapolis, IN 46241
Tel: (888) 248-1988 Fax: (317) 248-2014
www.sentechcorp.com

Your Cost _____ Prepared By _____ Date _____
F.O.B. Indianapolis Valid for 30 days from date