



## IR-SNIF-1,2,3 SPECIFICATIONS

<b>Size:</b>	10" x 12.5" x 4.75" (25.4cm x 31.2cm x 12cm)
<b>Weight:</b>	16 lbs. (7.2 kg)
<b>Power:</b>	120 or 240 Volt 50/60hz (41 Watts) (voltage must be specified at time of order)
<b>Temperature:</b>	32 deg F – 125 deg F (0 deg C – 50 deg C)
<b>Humidity:</b>	0 – 95 % non-condensing
<b>Atmospheric Pressure:</b>	75-106 Kpa Equipment rated for indoor use only
<b>Range:</b>	10 – 1000 ppm Standard
<b>Tube Length:</b>	0 – 250 ft (0 – 76 m)
<b>Trip Point:</b>	Low Alarm 0 – 1000 ppm Main Alarm 0 – 1000 ppm High Alarm 0 – 1000 ppm
<b>Leak Wait:</b>	Varies from seven (7) seconds to three (3) minutes depending on refrigerant concentration
<b>Alarm Output:</b>	Low, Main and High alarm relays, each with two (2) form C contacts rated 5 amps maximum
<b>Analog Output:</b>	0 – 10 volt proportional to 0 – 1000 ppm (4 – 20 mA optional)
<b>Computer Interface:</b>	RS-485 (optional)